





Apollo Carmix Equipments Private Limited (ACEPL) www.apollocarmix.com | info@apollocarmix.com

Ahmedabad-Mehsana State Highway,

Village : Rajpur 382 715, Dist. : Mehsana, Gujarat, India Phone : +91- 90990 71618 | +91- 90991 44644











Apollo Inffratech Group

India's Fastest Growing Construction Equipment Manufacturer

Apollo Inffratech Group is one of India's premier infrastructure backbone companies providing international standards and global technological breakthroughs to the Indian infrastructure companies. The group's adherence to quality and capabilities for global competency is clearly reflected in its supreme products. Blending quality, innovation and technology, Apollo offers world class products and services that encompass extensive market needs and thus is positioned as a leader in the market inspiring new trends and techniques.

In bid to continue offering world class concrete technologies to Indian customers, Apollo formed a joint venture company called Apollo Carmix Equipments Pvt Ltd (ACEPL) in 2013 with Carmix, Italy - a pioneer in the field - to manufacture and sell self-loading mobile concrete mixers in India to produce high-quality and cost-effective concrete at any job site.

ApolloCarmix has a state of the art facility located on Ahmedabad-Mehsana highway in Gujarat with fully functional R&D facilities to deliver innovatively designed, high quality world-class products. In fact, ApolloCarmix is the only 4x4 self loading concrete mixer manufacturer in India that offers Front Loading System to make operator's job easy. Some models also offer 270° Drum Rotation and Ground control through Remote for Drum Swivel, Drum Mixing & Discharge, Discharge Chute Up/Down and Auto Water Cutoff as per requirement.

Now with the growing distribution & dealership network, all ApolloCarmix equipment are backed by strong after - sales services. No doubt, ApolloCarmix SLMs are a first choice of contractors and infrastructure companies alike.

Apart from joint venture with Carmix, Italy, Apollo has entered into JV with HawkeyePedershaab, USA for concrete pipe making machines and Zenith, Germany, for integrated solutions for making concrete paver blocks & bricks, respectively formed Apollo HawkeyePedershaab Concrete Technologies Pvt. Ltd. & ApolloZenith Concrete Technologies Pvt. Ltd. Thus providing a complete range of world class concrete solutions under single roof to Indian infrastructure industry.

When it comes to modern infrastructure, Apollo's concrete solutions have no match in terms of quality, reliably and speed.



Easy & Economic Concrete Anywhere

Apollo Carmix JV started in the year 2013 with an Italian based group "Metalgalante S.p.A.", which is a world leader in Self-Loading Concrete Mixers under the brand name of "Carmix" manufacturing self-loading mobile concrete mixers for high-quality and cost-effective concrete solutions wherever and whenever required.

CARMIX was originated from CARMAN – a Company assembling parts and components supplied from old military and agricultural vehicles in early sixties. Many years and millions of cubic meters of concrete later, CARMIX customers started enjoying the world's best self-independent Self-loading Mixers. Today CARMIX is synonymous with 4×4 Self-Loading Concrete Mixers with supreme quality and unmatched reliability.

Furthermore Metalgalante is continuously revolutionizing the "mixer-concept": drum slewing 270°, the front cab, the hydraulically closed shovel, the joymix, the electronic weighing system and other smart innovations were all born at the home of CARMIX.

Outstanding versatility and cutting-edge equipment, these are the features that make Apollo Carmix such a valuable ally in tackling the most extreme operating conditions at any construction site.



46 FX 4.6 Cu.M. per batch*



30 FX 3.0 Cu.M. per batch*



23 FX 2.3 Cu.M. per batch*

ApolloCarmix

WORLD CLASS 4 X 4 SELF LOADING MOBILE CONCRETE MIXERS





4.3 TT 4.3 Cu.M. per batch*

Engine Mahindra & Mahindra
Ratings 112 HP@2200 rpm
Water cooled, Turbo Charged



3 TT 3.0 Cu.M. per batch*

Engine Mahindra & Mahindra

Ratings 74.5 HP@2200 rpm

Water cooled, Turbo Charged

(*@90 to 95% of the rated capacity)

WORLD's BEST: INDIA's FIRST

FRONT LOADING CONCRETE MIXERS

TT Series







270° Drum Rotation to discharge concrete on all 4 sides of the machine.



Joystick Operations for all main functions of loader for operators ease.



Easily Accessible Engine compared to various other mixers available in the market.



Ground control through Remote for Drum Swivel, Drum Mixing & Discharge, Discharge Chute Up/Down and Auto Water Cutoff as per requirement (& 3.TT only)

OPTIONAL:

- 1. IOT
- 2. Rear View Camera & Display

3. Loadcell (4.3 TT)

Apollo Carmix Self-loading Mixers


3TT & 4.3TT




TechSpecs

	MODEL >>>	ЗТТ	4.3TT		
	CHASSIS	Steel profile specially engineered	Steel profile specially engineered		
20004		for off-road operations	for off-road operations		
	MIXING UNIT	Concrete Output	Concrete Output		
S	Drum Volume	4080 ltrs.	5800 ltrs.		
Town	Capacity per batch	3.0 Cu.M	4.3 Cu.M		
		(@90 to 95% of the rated capacity)	(@90 to 95% of the rated capacity)		
	ENGINE	Mahindra & Mahindra	Mahindra & Mahindra		
Acres 1	Model	MCVNC35TI074CE5	MCVNC35TI112CE5		
	Ratings	74.5 HP@2200 rpm	112 HP@2200 rpm		
		Water cooled, Turbo Charged	Water cooled, Turbo Charged		
	SPEED	Electric Servo Control	Electric Servo Control		
4	Working Speed	0 to 9 Kms/hr	0 to 9 Kms/hr		
	Road Transfer	0 to 26 Kms/hr	0 to 26 Kms/hr		
- No	LOADING SHOVEL	400 ltrs	600 ltrs		
W.		with hydraulically operated shutter gate	with hydraulically operated shutter gate		
(A)	TYRES	Off Road Type	Off Road Type		
0	Size	12.5-20 PR 12	16/70-20 PR 16		
	STEERING	Hydraulic. 3 Way	Hydraulic. 3 Way.		
\mathcal{D}	Radius (internal)	1710 mm	1882 mm		
	Radius (external)	4650 mm	4800 mm		
	TANKS	Capacities	Capacities		
(II)	Water	2x270 ltrs	2x400 ltrs		
	Diesel	105 ltrs	115 ltrs		
	Hydraulic Oil	80 ltrs	80 ltrs		
Kg	WEIGHT	Equally distributed on both axles	Equally distributed on both axles		
		6750 Kgs.	8060 Kgs.		
64	ELECTRIC SYSTEM	12 Volt. 180 Ah battery for ele	ectric starter and road lighting.		
		Safety battery cut-off.			
-	CHUTE	Slewing and hydraulically tilting.			
	WATER SYSTEM	Colf contained Water Duran Water Mater Marker Walling Outlet			
	WATER STSTEIVI	Self contained Water Pump, Water Meter, Washing Outlet.			
	GRADIENT	Fully loaded 30% (16-17 degrees)			
D	DRIVING SEAT	Front Cabin on loading shovel-side. ROPS-FOPS cabin with double			
	101/07/07	closing door.			
413	JOY STICK	All hydraulic functions of shovel controlled by a single fully servo			
	OPERATION	controlled joy stick.			
With Apo	ollo's policy of constant upgradation o	f products, specifications are subject to change withou	ut prior notice.		

Accessories shown here are optional and not the part of standard supply.





	3 TT	4.3 TT
Α	1570	1620
В	2000	2380
С	1720	1720
D	6410	6910
Ε	1610	1630
F	3105	3290
G	372	395
Н	3850	4200
1	2190	2440
J	4000	4000

WORLD'S BEST 4X4 MOBILE SELF - LOADING CONCRETE MIXERS

FX Series













Double Helical Arrangement with low inclination of drum for better mixing.

Height and inclination angle adjustable Ecomatric Panel, comfortable for operator.

Easily Accessible Engine compared to various other mixers available in the market.

V- Shape articulated bucket with Hydraulic Shutter Gate to avoid spillage & better loading.

OPTIONAL:

1. IO

2. Rear View Camera & Display

Apollo Carmix Self-loading Mixers


23 FX, 30 FX & 46 FX



TechSpecs

	1				
	Model	23 FX	30 FX	46 FX	
de de	CHASSIS	Steel profile specially	y engineered for off-road	d	
	MIXING UNIT	Concrete output @90 to 95% of the rated capacity			
O	Drum Volume	3000 ltrs.	4080 ltrs.	6235 ltrs.	
	Capacity per batch	2.3 Cu.M.	3.0 Cu.M	4.6 Cu.M	
	ENGINE	Kirloskar Oil Ltd.	Mahindra & Mahindra	Mahindra & Mahindra	
Berny	Model	4R810T BSV	MCVNC35TI074CE5	MCVNC35TI112CE5	
	Ratings	49 HP@2200 rpm	74.5 HP@2200 rpm	112 HP@2200 rpm	
		Water cooled, Turbo Charged	Water cooled, Turbo Charged	Water cooled, Turbo Charged	
	SPEED	▼	Electric Servo Control		
42	Working Speed	0 to 10 Kms/hr	0 to 10 Kms/hr	0 to 9 Kms/hr	
	Road Transfer	0 to 27 Kms/hr	0 to 27 Kms/hr	0 to 26 Kms/hr	
® D	LOADING SHOVEL	400 ltrs	400 ltrs	600 ltrs	
0	TYRES	Off Road Type	Off Road Type	Off Road Type	
9	Size	12.5-20 PR 12	12.5-20 PR 12	16/70-20 PR 16	
	STEERING	Hydraulic. 3 Way.	Hydraulic. 3 Way.	Hydraulic. 3 Way.	
9	Radius (external)	4450 mm	4450 mm	4800 mm	
	TANKS	Capacities	Capacities	Capacities	
C y	Water	2x225 ltrs	2x275 ltrs	2x580 ltrs	
2.3	Diesel	95 ltrs	95 ltrs	130 ltrs	
	Hydraulic Oil	70 ltrs	70 ltrs	85 ltrs	
Кij	■ WEIGHT ■ Equally distribute			axles ————	
r-g		5600 Kgs.	5900 Kgs.	7790 Kgs.	
-	ELECTRIC SYSTEM	12 Volt. 150 Ah	12 Volt. 180 Ah	12 Volt. 180 Ah	
		battery for electric starter and road lighting. Safety battery cut-off.			
	CHUTE	Slewing and hydraulically tilting			
-	WATER SYSTEM	Self contained Water Pump, Water Meter, Washing Outlet.			
	GRADIENT	Fully loaded 30% (16-2	18 degrees)		
	DRIVING SEAT	Reversible seat with a	utomatic inversion of hy	draulic	
77		steering circuit	,		
JACH A	llo's policy of constant ungradation of	of products execifications are subject t			

With Apollo's policy of constant upgradation of products, specifications are subject to change without prior notice



	23 FX	30 FX	46 FX
Α	1700	1700	1810
В	1990	2100	2600
С	1380	1420	1610
D	6400	6710	7780
Е	1200	1420	1600
F	2720	2795	3210
G	385	385	390
Н	3470	3625	4200
	2190	2190	2440

ENGINEERED FOR RUGGED INDIAN TERRAINS



































